



大运
DAYUN



Vehicle category		Cargo truck
Driving type		4×2
Product platform		Autoplead Light Truck
Steering wheel position		Left Hand Driving
Product parameters		Cargo box
Vehicle Model		PG01FK33E9NA57JJ00PE
Vehicle dimension parameters	Wheelbase	3300
	Vehicle dimension (L × W × H)	5995×2090×2300
	Cargo body dimension (L × W × H)	4100*2000*1900
	Wheel track (front / rear) (mm)	1590/1540
	Minimum ground clearance (mm)	220
Vehicle quality parameters	Complete vehicle kerb mass (kg)	2540
	Chassis kerb weight (kg)	2130
	Calibrated (fifth wheel) payload mass (kg)	1750
	Calibrated gross mass (kg)	4485
Vehicle performance parameters	Max. speed	108
	Max. gradeability ,% (full load)	≥30
Product configuration		
Cabin	Type	Single Cabin
	Carrying capacity	3
Engine	Brand	Isuzu
	Model	JE493ZLQ3A
	Max power (ps)	102
	Series	Eur III
	Displacement (L)	2.771
	Rated rpm	3400
Clutch	Type	diaphragm type
Gearbox	Brand	Wan Liyang
	Model	5T92
Braking	Service brake	Air pressure braking
	Parking brake	Parking air-cutoff brake
Suspension	Number of front suspensions/ leaf springs	9
	Number of rear suspensions/ leaf springs	9+6
Front axle	Rated load	2500Kg

front axle	Brake type		Drum-type braking
Middle / rear axle	Tonnage		3500Kg
	Structure		welding-type axle
	Gear ratio		i=5.571
Tire	Plate parameter (mm)		7.00R 16LT
	Quantity		7
Frame	External width (mm)		800
	Stringer gross section (mm)		180
Steering engine	Model		K49(Ø74)
Fuel tank	Specifications and Materials		iron fuel tank
Electrical system	Rated voltage		12V
	Battery		150Ah
Function configuration	Front suspension	Spiral spring	●
	Rear suspension	Spiral spring	●
	Body inversion	Manual hydraulic	●
	Bumper	Medium bumper	●
	Rear view mirror	Manual rearview	●
	Seat	Machinery	●
	Doors and windows	Electric windows and doors	●
		Central locking	●
	Meter	Combination meter	●
	Entertainment	MP3 + Radio	●
	Air conditioner	Manual	●
Installation configuration	Flow guide cover		●
● Standard configuration ○ Optional equipment - No such configuration			